



1890ENH

Part Number: 1890ENH

Category 7A Nonbonded-Pair ScTP Cable

Product Description

CAT7A (1000MHz) shotgun, 2 x 4-Pair, S/FTP shielded, Premise Horizontal Cable, 22 AWG solid bare copper conductors, Foam Polyolefin insulation, each pair with Beldfoil® shield, overall tinned copper braid shield (50% coverage), LSZH jacket

Product Specifications

Technical Specifications

Application 1:	Horizontal and building backbone cable
Application 2:	Support current and future Category 6a, 7 and 7a applications: 10GBase-T (10 Gigabit Ethernet), 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI, ATM

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Material	No. of Pairs
Individual shielded pair	22	Solid	Bare copper	8

Min Elongation at Breakof Conductors:	10 %
--	------

Insulation:

Element	Type	Material	Nominal Diameter
Individual shielded pair	Dielectric	Foamed polyethylene	1.54 mm

Min Elongation at Breakof Insulation:	100 %
--	-------

Color Chart 1:

Number	Color
--------	-------

Pair 1	White & Blue
Pair 2	White & Orange
Pair 3	White & Green
Pair 4	White & Brown

Innershield:

Element	Type	Material	Coverage
Individual shielded pair	Tape	Aluminium / Polyester	100 %
Aluminum facing outside			

Outershield 1:

Type	Material	Min. Coverage
Braid	Tinned copper	30 in

Outerjacket 1:

Element	Material	Nominal Diameter	Diameter +/- Tolerance	Ripcord
	FRNC / LSNH	8.1 mm	0.3 mm	Yes
Figure 8 construction				
Min Elongation at Break of Jacket:		100 MPa		
Min Tensile Strength of Jacket:		9 lbs		

Electrical Characteristics

Conductor DCR:

Max. Conductor DCR	Max DCR Unbalanced Between Pairs	Max. DCR Unbalanced Within Pair
95 Ohm/100m	4 %	2 Ohm

Capacitance:

Max. Capacitance Unbalanced	Max. Mutual Capacitance
1,600 pF/m	56 pF/m
Min Insulation Resistance:	5000 mOhm/1000ft

Impedance:

Nominal Characteristic Impedance
100 mOhm/ft

Delay:

Max. Delay Skew	Nominal Velocity of Propagation (VP)
25 ns/100m	78 ns/100m

High Freq:

Element	Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT	Min. PSNEXT	Min. ACR	Min. PSACR	Min. ACRF (ELFEXT)	Min. PSACRF (PSELFEXT)	Min. RL (Return Loss)	Min. PSANEXT	Min. PSAACRF	Min. ELTCL	Min. ELTCTL
	1 MHz	2.1 db/100m	78 dB	75 dB	75.9 dB	72.9 dB	78 dB	75 dB	20 dB	67 dB	67 dB	40 dB	23 dB
	4 MHz	3.7 db/100m	78 dB	75 dB	74.3 dB	71.3 dB	78 dB	75 dB	23 dB	67 dB	67 dB	34 dB	15 dB
	10 MHz	5.8 db/100m	78 dB	75 dB	72.2 dB	69.2 dB	75.3 dB	72.3 dB	25 dB	67 dB	67 dB	30 dB	10.9 dB
	16 MHz	7.3 db/100m	78 dB	75 dB	70.7 dB	67.7 dB	71.2 dB	68.2 dB	25 dB	67 dB	67 dB	28 dB	5.1 dB
	31.2 MHz	10.3 db/100m	78 dB	75 dB	67.7 dB	64.7 dB	65.4 dB	62.4 dB	23.6 dB	67 dB	63.3 dB	25.2 dB	
	62.5 MHz	14.6 db/100m	78 dB	75 dB	63.4 dB	60.4 dB	59.4 dB	56.4 dB	21.5 dB	67 dB	57.3 dB	22 dB	
	100 MHz	18.5 db/100m	75.4 dB	72.4 dB	56.9 dB	53.9 dB	55.3 dB	52.3 dB	20.1 dB	67 dB	53.2 dB	20 dB	
	155 MHz	23.2 db/100m	72.5 dB	69.5 dB	49.3 dB	46.3 dB	51.5 dB	48.5 dB	18.8 dB	67 dB	49.4 dB	18.1 dB	
	250 MHz	29.7 db/100m	69.4 dB	66.4 dB	39.7 dB	36.7 dB	47.3 dB	44.3 dB	17.3 dB	67 dB	45.2 dB	16 dB	
	500 MHz	42.8 db/100m	64.9 dB	61.9 dB	22.2 dB	19.2 dB	41.3 dB	38.3 dB	17.3 dB	67 dB	39.2 dB		
	600 MHz	47.1 db/100m	63.7 dB	60.7 dB	16.6 dB	13.6 dB	39.7 dB	36.7 dB	17.3 dB	65.8 dB	37.6 dB		
	1000 MHz	61.9 db/100m	60.4 dB	57.4 dB	-1.5 dB	-4.5 dB	35.3 dB	32.3 dB	15.1 dB	62.5 dB	33.2 dB		
	1200 MHz	68.4 db/100m	59.2 dB	56.2 dB	-9.1 dB	-12.1 dB	33.7 dB	30.7 dB	14.3 dB				

): Limits below 4MHz are for information only;): Values at 1000 MHz are for information only

Current:

Max. Recommended Current
1.5 A

Voltage:

Voltage Rating

72 dB

Coupling Attenuation:

Coupling Attenuation

Type IV

Transfer Impedance:

Frequency [MHz]	Description	Transfer Impedance
1 Mhz	Grade 1	Max. 10 mOhm/m
10 Mhz		Max. 10 mOhm/m
30 Mhz		Max. 30 mOhm/m
100 Mhz		Max. 100 mOhm/m

Use

Burning Load:	1000 kJ/m
Max Recommended Pulling Tension:	170 lbs

Safety

ISO/IEC Flammability:	IEC 60332-1
Amt of Halogen Acid Gas; MaxConductivity:	10 μ S/mm
Amt of Halogen Acid Gas; Min pH:	4.3
Smoke Density; Min Transmittance:	60 %
Amt of Halogen IEC 60754-1 /EN50267-1:	Zero

Temperature Range

Installation Temp Range:	0 to +50 °C
Operating Temp Range:	-30 to +60 °C

Mechanical Characteristics

Min Bend Radius During Installation:	58 mm
Min Bend Radius During Operation:	29 mm

Part Number

Standards

ISO/IEC Compliance:	ISO/IEC 11801 2nd edition (2002) and ISO/IEC 11801 Amendment 2 (2010)
CENELEC Compliance:	EN 50173-1 (2011)

History

Revision Date:	40994
Revision Number:	3

Product Variants

Part Number	Color	Put-Up Type	Length
1890ENH.00500	GRAY	Reel	500 m

© 2015 Belden, Inc.

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.