



## 2412

**Part Number:** 2412

Enhanced Category 6 Nonbonded-Pair Cables

## Product Description

CAT6+ (300MHz), 4-Pair, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Tape Separator, Ripcord, PVC Jacket

## Product Specifications

## Technical Specifications

### Product Description

### Application

**Suitable Applications:**

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM

### Classification

### Construction and Dimensions

**Conductor:**

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

### Conductor

**Total Number of Conductors:**

8

**Insulation:**

**Material**

PO - Polyolefin

## Insulation

---

### Color Chart 1:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

## InnerShield

---

## Cabling<sup>1</sup>

---

### Outershield 1:

Material
Unshielded

### Outerjacket 1:

Material	Nominal Diameter	Min. Wall Thickness	Ripcord	Separator Material
PVC - Polyvinyl Chloride	0.225 mm	0.01 mm	Yes	Patented Dielectric Tape

## OuterJacket<sup>1</sup>

---

## OuterJacket<sup>2</sup>

---

## Part Number

---

## Static Ground

---

## Tracer

---

## Electrical Characteristics

---

### Conductor DCR:

Max. Conductor DCR	Max. DCR Unbalance
8.2 Ohm/100m	5 %

## Capacitance:

### Nominal Mutual Capacitance

17 pF/ft

## General Electrical Parameters

### Delay:

#### Max. Delay Skew

#### Nominal Velocity of Propagation (VP)

45 ns/100m

70 ns/100m

### High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT	Min. PSNEXT	Min. ACR	Min. PSACR	Min. ACRF (ELFEXT)	Min. PSACRF (PSELFEXT)	Min. RL (Return Loss)	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2 db/100m	75.3 dB	73.3 dB	73.3 dB	71.3 dB	70.8 dB	67.8 dB	20 dB	100 ± 15 Ohm	102 ± 15 Ohm
4 MHz	3.7 db/100m	66.3 dB	64.3 dB	62.6 dB	60.6 dB	58.8 dB	55.8 dB	23 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	5.2 db/100m	63.3 dB	61.3 dB	58.1 dB	56.1 dB	52.7 dB	49.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	5.8 db/100m	61.8 dB	59.8 dB	56 dB	54 dB	50.8 dB	47.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	7.4 db/100m	58.6 dB	56.6 dB	51.2 dB	49.2 dB	46.7 dB	43.7 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	8.3 db/100m	57.1 dB	55.1 dB	48.8 dB	46.8 dB	44.8 dB	41.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	9.3 db/100m	55.5 dB	53.5 dB	46.3 dB	44.3 dB	42.8 dB	39.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	10.4 db/100m	54 dB	52 dB	43.6 dB	41.6 dB	40.9 dB	37.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	15 db/100m	49.1 dB	47.1 dB	34.1 dB	32.1 dB	34.9 dB	31.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	19.3 db/100m	45.8 dB	43.8 dB	26.5 dB	24.5 dB	30.8 dB	27.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	24.5 db/100m	42.7 dB	40.7 dB	18.2 dB	16.2 dB	27 dB	24 dB	19.5 dB	100 ± 22 Ohm	100 ± 15 Ohm
200 MHz	28.3 db/100m	40.9 dB	38.9 dB	12.6 dB	10.6 dB	24.8 dB	21.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.1 db/100m	39.3 dB	37.3 dB	7.2 dB	5.2 dB	22.8 dB	19.8 dB	18 dB	100 ± 32 Ohm	100 ± 15 Ohm

300 MHz	35.6 db/100m	38.1 dB	36.1 dB	2.5 dB	-0.5 dB	21.3 dB	18.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm
350 MHz	38.9 db/100m	37.1 dB	35.1 dB	-1.7 dB	-3.7 dB	19.9 dB	16.9 dB	17 dB		
400 MHz	42 db/100m	36.3 dB	34.3 dB	-5.7 dB	-7.7 dB	18.8 dB	15.8 dB	16.6 dB		
450 MHz	45 db/100m	35.5 dB	33.5 dB	-9.5 dB	-11.5 dB	17.7 dB	14.7 dB	16.2 dB		
500 MHz	47.9 db/100m	34.8 dB	32.8 dB	-13 dB	-15 dB	16.8 dB	13.8 dB	15.9 dB		
550 MHz	50.6 db/100m	34.2 dB	32.2 dB	-16.4 dB	-18.4 dB	16 dB	13 dB	15.6 dB		

## Voltage:

### UL Voltage Rating

300V RMS

## Coupling Attenuation

## Screening

## Transfer Impedance

## Use

Max Recommended Pulling Tension: 40 lbs

## Material

## Safety

C(UL) Flammability:	FT4
CSA Flammability:	FT4
UL Flammability:	UL1666 Riser

## Temperature Range

Installation Temp Range:	+5°C To +50 °C
Operating Temp Range:	0°C To +75°C
Storage Temp Range:	-20°C To +75 °C

## Mechanical Characteristics

---

### Bend Radius

---

Min Bend Radius/Minor Axis:	0.9 in
Min Bend Radius/Installation:	2.25 in

### Crush Resistance

---

### Connectors

---

### Stripping Performance

---

### EU Directive

---

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes

### Part Number

---

Plenum (Y/N):	No
Plenum Number:	2413

### Applicable Patents

---

Country:	US
Patent:	7977575

### Standards

---

ISO/IEC Compliance:	11801 ed 2.1 (2008) Class E
Telecommunications Standards:	ANSI/TIA/EIA 568 C.2 Category 6
CA Prop 65 (CJ for Wire & Cable):	Yes
CEC/C(UL) Specification:	CMR
MII Order #39 (China RoHS):	Yes
NEC/(UL) Specification:	CMR
Other Specification:	Third party verified to Category 6

### Contact Information

---

PHONE\_NUM:

1-800-Belden1

## History

---

## Usage

---

## Put Ups and Colors

---

**Notes:**

Jacket sequentially marked at 2 ft./1m intervals. Third party verified to ANSI/TIA-568-C.2, Category 6. Values above 300 MHz are for Engineering Informaton Only. In addition to the colors below, Pink is also available as a special, p/n 2412 012 U1000, or 2412 012 A1000.

© 2015 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.