



2424

Part Number: 2424

Enhanced Category 6 Nonbonded-Pair Cables

Product Description

CAT6+ (300MHz), 4-Pair, U/UTP-Unshielded, Zero Halogen, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Patented Tape Separator, Ripcord, LSZH Jacket.

Product Specifications

Technical Specifications

Product Description

Application

Suitable Applications:

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

Classification

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Conductor

Total Number of Conductors:

8

Insulation:

Material

PO - Polyolefin

Insulation

Color Chart 1:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

InnerShield

Cabling¹

Outershield 1:

Material

Unshielded

Outerjacket 1:

Material	Nominal Diameter	Ripcord	Separator Material
LSZH - Low Smoke Zero Halogen	0.221 mm	Yes	Patented Dielectric Tape

OuterJacket¹

OuterJacket²

Part Number

Static Ground

Tracer

Electrical Characteristics

Conductor DCR:

Max. Conductor DCR

Max. DCR Unbalance

9.38 Ohm/100m	5 %
---------------	-----

Capacitance:

Nominal Mutual Capacitance
17 pF/ft

General Electrical Parameters

Delay:

Max. Delay Skew	Nominal Velocity of Propagation (VP)
45 ns/100m	70 ns/100m

High Freq:

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT	Min. PSNEXT	Min. ACR	Min. PSACR	Min. ACRF (ELFEXT)	Min. PSACRF (PSELFEXT)	Min. RL (Return Loss)	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
0.772 MHz	1.8 db/100m	77 dB	75 dB	75.2 dB	73.2 dB	73 dB	70 dB			102 ± 15 Ohm
1 MHz	2 db/100m	75.3 dB	73.3 dB	73.3 dB	71.3 dB	70.8 dB	67.8 dB	20 dB	100 ± 15 Ohm	102 ± 15 Ohm
4 MHz	3.7 db/100m	66.3 dB	64.3 dB	62.6 dB	60.6 dB	58.8 dB	55.8 dB	23 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	5.2 db/100m	63.3 dB	61.3 dB	58.1 dB	56.1 dB	52.7 dB	49.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	5.8 db/100m	61.8 dB	59.8 dB	56 dB	54 dB	50.8 dB	47.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	7.4 db/100m	58.6 dB	56.6 dB	51.2 dB	49.2 dB	46.7 dB	43.7 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	8.3 db/100m	57.1 dB	55.1 dB	48.8 dB	46.8 dB	44.8 dB	41.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	9.3 db/100m	55.5 dB	53.5 dB	46.3 dB	44.3 dB	42.8 dB	39.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	10.4 db/100m	54 dB	52 dB	43.6 dB	41.6 dB	40.9 dB	37.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	15 db/100m	49.1 dB	47.1 dB	34.1 dB	32.1 dB	34.9 dB	31.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	19.3 db/100m	45.8 dB	43.8 dB	26.5 dB	24.5 dB	30.8 dB	27.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	24.5 db/100m	42.7 dB	40.7 dB	18.2 dB	16.2 dB	27 dB	24 dB	19.5 dB	100 ± 22 Ohm	100 ± 15 Ohm
200 MHz	28.3 db/100m	40.9 dB	38.9 dB	12.6 dB	10.6 dB	24.8 dB	21.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm

250 MHz	32.1 db/100m	39.3 dB	37.3 dB	7.2 dB	5.2 dB	22.8 dB	19.8 dB	18 dB	100 ± 32 Ohm	100 ± 15 Ohm
300 MHz	35.6 db/100m	38.1 dB	36.1 dB	2.5 dB	-0.5 dB	21.3 dB	18.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm
350 MHz	38.9 db/100m	37.1 dB	35.1 dB	-1.7 dB	-3.7 dB	19.9 dB	16.9 dB	17 dB		
400 MHz	42 db/100m	36.3 dB	34.3 dB	-5.7 dB	-7.7 dB	18.8 dB	15.8 dB	16.6 dB		
450 MHz	45 db/100m	35.5 dB	33.5 dB	-9.5 dB	-11.5 dB	17.7 dB	14.7 dB	16.2 dB		
500 MHz	47.9 db/100m	34.8 dB	32.8 dB	-13 dB	-15 dB	16.8 dB	13.8 dB	15.9 dB		
550 MHz	50.6 db/100m	34.2 dB	32.2 dB	-16.4 dB	-18.4 dB	16 dB	13 dB	15.6 dB		

Voltage:

UL Voltage Rating

300V RMS

Coupling Attenuation

Screening

Transfer Impedance

Use

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No
Max Recommended Pulling Tension:	40 lbs

Material

Safety

ISO/IEC Flammability:	60332-1
Suitability - Non-Halogenated:	Yes

Temperature Range

Operating Temp Range:	-20°C To +75°C
-----------------------	----------------

Mechanical Characteristics

Bend Radius

Min Bend Radius/Minor Axis:	0.9 in
Min Bend Radius/Installation:	2.2 in

Crush Resistance

Connectors

Stripping Performance

EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes

Part Number

Plenum (Y/N):	No
Plenum Number:	2413

Applicable Patents

Country:	US
Patent:	7977575

Standards

ISO/IEC Compliance:	11801 ed 2.1 (2008) Class E
Telecommunications Standards:	ANSI/TIA/EIA 568 C.2 Category 6
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

History

Usage

Put Ups and Colors

Notes:	Jacket sequentially printed with dual footage and meter markings. Third party verified to ANSI/TIA-568-C.2, Category 6. Values above 300 MHz are for Engineering Informaton Only.
---------------	---

© 2015 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.